

MD1JB

SOLENOID OPERATED DIRECTIONAL CONTROL VALVES


ALTERNATING CURRENT SERIES 10

NFPA D03 (ISO 4401-03 / CETOP 03)


p max 5000 psi

Q max 18 GPM

MOUNTING INTERFACE



OPERATING PRINCIPLE




PERFORMANCES (with mineral oil of viscosity of 36 cSt at 50°C)

Maximum operating pressure Ports P - A - B Port T	psi	5000 2000
Maximum flow rate	GPM	18
Pressure drop $\Delta p-Q$	see paragraph 4	
Operating limits	see paragraph 6	
Electrical features	see paragraph 7	
Electrical connections	junction box	
Ambient temperature range	°F	-4 / +125
Fluid temperature range	°F	-4 / +175
Fluid viscosity range	cSt	10 - 400
Fluid contamination degree	according to ISO 4406:1999 class 20/18/15	
Recommended viscosity	cSt	25
Masse: single solenoid valve double solenoide valve	lbs	4.4 3.3

- The valve body (1) is made with high strength iron castings provided with wide internal passages in order to minimize the flow pressure drop. Wet armature solenoids (2) with easily removable interchangeable coils (3) are used (for further information on solenoids see par. 7). It is supplied with junction box (5) for the electrical connection.
- The valve is supplied with 3 or 4 way designs and with several interchangeable spools (4) with different porting arrangements.
- The valve is available with AC solenoids.



1 - IDENTIFICATION CODE



2 - HYDRAULIC FLUIDS


Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals (code N). For fluids HFDR type (phosphate esters) use FPM seals (code V). For the use of other fluid types such as HFA, HFB, HFC, please consult our technical department.

Using fluids at temperatures higher than 175 °C causes a faster degradation of the fluid and of the seals characteristics. The fluid must be preserved in its physical and chemical characteristics.

3 - CONFIGURATIONS


Type S:

3 positions with spring centering




Type *TA:

2 positions with return spring




Type *TC:

2 positions with return spring




Type TA:

2 positions with return spring




Type TC:

2 positions with return spring





Type RK:

2 positions with mechanical retention



Model 32TA/32TC:

3-way valve - 1 solenoid - 2 external position, return spring




Besides the diagrams shown, which are the most frequently used, other special versions are available: consult our technical department for their identification, feasibility and operating limits.



MD1JB


SERIES 10

4 - PRESSURE DROP Δp -Q (obtained with viscosity of 170 SSU at 120°F)



PRESSURE DROPS WITH VALVE ENERGIZED

SPOOL TYPE	FLOW DIRECTION			
	P-A	P-B	A-T	B-T
	CURVES ON GRAPH			
S1, 1TA, 1TC	1	1	2	2
S2, 2TA, 2TC	5	5	4	4
S3, 3TA, 3TC	1	1	4	4
S4, 4TA, 4TC	6	6	7	7
S5	1	5	2	2
S6	1	1	2	4
S7	5	6	7	7
S8	6	5	7	7
S9	1	1	2	2
S10	5	5	2	2
S11	1	1	4	2
S18	5	1	2	2
TA, TB	1	1	2	2
TA02, TB 02	1	1	2	2
32TA, 32TC	3	3		
RK	1	1	2	2



PRESSURE DROPS WITH VALVE IN DE-ENERGIZED POSITION

SPOOL TYPE	FLOW DIRECTION				
	P-A	P-B	A-T	B-T	P-T
	CURVES ON GRAPH				
S2, SA2, SB2					3*
S3, SA3, SB3			7 [■]	7 [○]	
S4, SA4, SB4					7
S5		7			
S6				7	
S7					7 [○]
S8					7 [■]
S9					
S10	7 [■]	7 [○]			
S11			7		
S18	7				

* A-B blocked ■ B blocked ○ A blocked

5 - SWITCHING TIMES

The values indicated refer to an S1 solenoid valve for Q=13 GPM, p=2,000 psi working with mineral oil at a temperature of 120 °F, a viscosity of 170 SSU and with PA and BT connections. The energizing times are obtained at the time the spool switches over. The de-energizing times are measured at the time pressure variation occurs on the line.


TIMES (±10%)	ENERGIZING	DE-ENERGIZING
AC solenoid	10 ÷ 25 ms	20 ÷ 40 ms



6 - OPERATING LIMITS

The curves define the flow rate operating fields according to the solenoid valve pressure with AC solenoids.

The values have been obtained with viscosity 170 SSU, temperature 120 °F, filtration 25 µm and with solenoids at rated temperature and supplied with voltage equal to 90% of the nominal voltage.



SPOOL TYPE	CURVE	
	P-A	P-B
S1,1TA,1TC	1	1
S2, 2TA, 2TC	1	1
S3, 3TA, 3TC	2	2
S4, 4TA, 4TC	3	3
S5	1	1
S6	2	2
S7	3	3
S8	3	3

SPOOL TYPE	CURVE	
	P-A	P-B
S9	3	3
S10	1	1
S11	2	2
S18	1	1
TA, TC	1	1
TA02, TB02	1	1
32TA, 32TB	1	1
RK	1	1

The values indicated in the two graphs can be considerably reduced if a 4-way valve is used as a 3-way valve with port A or B plugged or without flow.

For valves having supply voltage of 120V-60Hz or 240V-60Hz performances may be slightly higher than the ones showed in the diagram.



7 - ELECTRICAL FEATURES

7.1 Solenoids

These are essentially made up of two parts: tube and coil. The tube is threaded onto the valve body and includes the armature that moves immersed in oil, without wear. The inner part, in contact with the oil in the return line, ensures heat dissipation.

The coil is fastened to the tube by a threaded nut.

The interchangeability of coils of different voltages is allowed.

SUPPLY VOLTAGE FLUCTUATION	± 10% Vnom
MAX. SWITCH ON FREQUENCY	10.000 ins/hr
DUTY CYCLE	100%
Class of protection according to CEI EN 60529 Atmospheric agents Coil insulation Impregnation	IP 65 class H class F

7.2 Current and absorbed power


In alternating current energizing, an initial phase (maximum movement) is seen, during which the solenoid consumes elevated value currents (inrush current); the current values diminish during the plunger stroke until it reaches the minimum values (holding current) when the plunger reaches the stroke end.

Coils (values ± 5%)

Type of coil	Frequency [Hz]	Nominal voltage [V]	Resistance at 20°C [Ohm]	Current consumption at inrush [A]	Current consumption at holding [A]	Power consumption at inrush [VA]	Power consumption at holding [VA]	Code
C20.6-A120-60K6/10	60	110	27,5	1,8	0,36	198	39,6	1902820
		120		2	0,43	240	51,6	
C20.6-A240-60K6/10		220	110	0,86	0,17	189,2	37,4	1902821
		240		0,98	0,2	235,2	48	


8 - INSTALLATION

Configurations with centering and return springs can be mounted in any position; type RK valves - without a spring and with mechanical retention - must be mounted with the longitudinal axis horizontal. Valve fitting takes place by means of screws or tie rods, laying the valve on a lapped surface, with values of planarity and smoothness that are equal to or better than those indicated in the drawing. If the minimum values of planarity or smoothness are not met, fluid leakages between valve and mounting surface can easily occur. For use in tropical climates, it is necessary to include the CM option.




9 - OVERALL AND MOUNTING DIMENSIONS


MD1JB - S
MD1JB - RK



MD1JB - TA



Drawing view in compliance with ISO 128




dimensions in inches

1	Coil removal space
2	Mounting surface with sealing rings
3	Manual override
4	Junction box
5	CM manual override, boot protected

See par. 10 and 11 for sealing rings and fastening bolts



10 - SPARE PARTS



1	Coil locking ring - code 0119333
2	O-Ring type 2-019 (2081) - 70 shore
3	Coil (see identification code on the side)
4	2 O-Ring type 3-910 - 70 shore
5	Solenoid tubes: TA20.6-M18/10N (NBR seals) TA20.6-M18/10V (FPM seals) NOTE: the tube is supplied with O-Ring rif. 7
6	O-Ring type 2-016 (2062) - 70 shore
7	Seal for junction box cod. 0119407
8	Junction box: EJB3-D/10 (double solenoid valve) EJB3-SA/10 (single solenoid valve MD1JB-TA/10) EJB3-SB/10 (single solenoid valve MD1JB-TC/10)
9	2 bolts M3x25
10	4 O-Ring type 2-012 (2037) - 90 shore

COILS IDENTIFICATION CODE

C 20.6 - K6 / 10

Supply voltage _____
A120-60 = 110/120 V - 60 Hz
A240-60 = 220/240 V - 60 Hz

Series no.
 (the overall and mounting
 dimensions remain
 unchanged from 10 to 19)

Coil electrical connection:
 2 pins for junction box

SEALS KIT

The codes here below include O-Rings ref.2, 4, 6 and 10.

Cod. 1985408 NBR seals
Cod. 1985409 FPM (viton) seals

11 - FASTENING BOLTS

4 bolts type 10-24 UNC - 2Bx2
 Tightening torque 53 lbs·inch



DIPLOMATICO OLEODINAMICA S.p.A.
 20015 PARABIAGO (MI) • Via M. Re Depaolini 24
 Tel. +39 0331.895.111
 Fax +39 0331.895.339
 www.diplomatic.com • e-mail: sales.exp@diplomatic.com

UNIVERSAL HYDRAULICS INT'L LTD

9337 Ravenna Road, Unit G,
 TWINSBURG, OHIO 44087
 Phone +330-405-1800 - Fax +330-405-1801
 E-mail: diplomatic@uhiltd.com